

POND SEALER

SODIUM BENTONITE POND SEALANT



DESCRIPTION $\frac{1}{4}$ " Size and smaller down to dust size

Pond Sealer is a high swelling chemically unaltered sodium bentonite that contains no additives. It is an economical way to accomplish pond and lake sealing to reduce seeping losses.

Sodium Bentonite is a natural clay which has the characteristic of swelling many times its dry size when it become wet. When bentonite is applied in a layer over porous soil or mixed with a porous soil, and then, moistened with water, it forms an impermeable layer. Bentonite does not affect the water or the wildlife.

APPLICATION

Pond Sealer can be applied directly to the soil in the bottom of the lake or pond. If conditions necessitate, sprinkling the bentonite through water, to the bottom, we recommend using Granular Seal, which contains no powder. Treatment is usually more effective if the bentonite is applied directly to the soil. The sprinkle method is recommended only when it is impractical to drain the water from the area to be treated.

<u>Soil Type</u>	<u>lbs per ft²</u>
Clay	1.5
Sandy Silt	2.5
Silty Sand	3.0
Clean Sand	4.0
Rock or Gravel	5.0

PACKAGING

Available in 50 lb polyethylene bags, 3,000 lbs bulk bags and bulk loads

PERMEABILITY 1.9×10^{-9} cm/sec

CHEMICAL ANALYSIS

SiO ₂	66.60	%
Al ₂ O ₃	17.60	%
Fe ₂ O ₃	3.67	%
CaO	0.57	%
MgO	1.80	%
Na ₂ O	2.50	%
K ₂ O	0.31	%
Bound Water	6.51	%
Moisture at 20 ^o F	0.14	%

X-RAY ANALYSIS

Montmorillonite	85	%
Quartz	5	%
Feldspars	5	%
Cristobalite	2	%
Illite	2	%
Calcium & Gypsum	1	%

** Approximately 2000 lbs. per cubic yard when dry **

EASLEY, INC.

12160 NS 3610 Seminole, OK 74868 USA . Tel: (405) 382-1973

easleyinc.com - e-mail: easleym@hughes.net